

TRANSFORMING AIR PURIFICATION

750+ wall mount



What's in the Plus?

Only Greentech has the filters with the plus.

Our MERV-rated pleated filters treated with

ODOGard® coating traps and inactivates

pathogens and allergens. ODOGard instantly

bonds to odor molecules and changes their

molecular structure, completely clearing rooms

of odors in under 10 minutes.

Applications::

Active Air Purifier with PCO & ODOGard® Technology

Workshops • Offices • Schools

Day Care Facilities • Nursing Homes • Nail Salons •

Veterinary Clinics • Motor Coaches Public Restrooms

Features:

- · Active Air Purification
- No Ductwork Required
- Easily Mounts to Wall
- 24/7 Odor and Particulate Reduction
- Replaceable PCO Cell and MERV+ Filter

Benefits of Greentech's 750+ Wall Mount



Continuous Purification



Reduces Odors



Mounts to Save Space



Sized for Multiple Locations



Wide List of Applications

Active Oxidation Improves Air Quality



Providing continuous air purification, this permanently mounted unit is perfect for spaces without HVAC duct access. Greentech's 750+ Wall Mount features the same active air purification technology developed and used by NASA.



AOPs are propelled out into your space to hunt down particulates, even the very small ones. At the same time, negative ions go out and charge particles such as dust, pollen and pet dander, causing them to drop out of your breathing space.



Photocatalytic oxidation (PCO) technology uses energy to activate a catalyst, turning moisture into products that continuously clean your space.



Our MERV+ filters have an ODOGard® coating that eliminates odors at the molecular level, making it impossible for the odor to survive. Even the toughest, seemingly permanent odors don't stand a chance against ODOGard.

Features and Specifications

UNIT

- Models: Greentech SIREN 750+ Wall Mount 1X5789
 Greentech 750+ Wall Mount NO3 (no ozone) 1X5821
- Dimensions: 11.92" H x 9.72" W x 3.64" D
- Metric: 303mm H x 247mm W x 93mm D
- Weight: 3.3lbs (1.5kg)
- Materials: Powder Coated Aluminum
- Unit Warranty: 2 Year Manufacturer's Warranty

PERFORMANCE

- Airflow: 70 CFM
- Optional Ozone Output: < 0.05 ppm
- Coverage: up to 750 ft²

POWER

- Input Voltage: 24VDC
- Operating Voltage 24VDC
- Supply Power: 120-240VAC | 17W
- Operating Power: 24VDC | .67A

TECHNOLOGIES

- PCO: Photocatalytic Oxidation
- ODOGard® Coated MERV+ Filter
- Bipolar Ionization Module (BPI)
- Activated Oxygen (Ozone) Optional

To Use This Product Correctly



Read All Instructions Carefully in User Manual Before Operating Purifier.